

Communication and Charging cradle for CASIO IT-800 / DT-X7 / DT-X8 with extra features



CU-800/CU-800-EC
HA-H601O Compatible



CU-X7
HA-F601O Compatible



CU-970
HA-N601O Compatible



CU-X8
HA-K601O Compatible



Additional Features

- ✓ Powerless connection with CASIO IT-800 / DT-X7 / DT-X8 - no power adapter is needed for communication
- ✓ Support USB memory stick data transfer
- ✓ Ultra slim and exquisite streamline enclosure
- ✓ External Battery Charger option for IT-800 Battery (CU-800 only)

Communication and Charging cradle for CASIO IT-800 / DT-X7 / DT-X8 with extra features



Communication Cradle
(Bundle USB cable)
CU-X7
Compatible HA-F60IO



Communication Cradle
(Bundle USB cable)
CU-800
Compatible HA-H60IO



Communication Cradle
(Bundle USB cable)
CU-970
Compatible HA-N60IO



Optional Battery Charger
(for CU-800 only)
CU-800-EC



Communication Cradle
(Bundle USB cable)
CU-X8
Compatible HA-K60IO



Communication Cradle with Optional Charger
(Bundle USB cable)
CU-800/CU-800-EC

Power Adapter Options



AC/DC Wall Mount Power Adaptor 12VDC/2000mA (UK type)
ADA-SAW24-12-2000-W



AC/DC Desktop Power Adaptor 12VDC/2000mA
(for overseas countries)
ADA-SAW24-12-2000-D

Specifications

	CU-800	CU-800-EC	CU-800/CU-800-EC	CU-X7	CU-X8	CU-970
Dimensions and Weight						
Dimension (mm)	69(L) x 100(W) x 86(H)	70(L) x 73(W) x 46(H)	130(L) x 100(W) x 86(H)	77(L) x 82(W) x 86(H)	90(L) x 100(W) x 105(H)	69(L) x 100(W) x 86(H)
Weight	150g	60g	210g	150g	150g	220g
Interface						
USB Host Port USB Client Port	Maximun 12Mbps					
Environment						
Operation Temp.	0°C to +40°C					
Storage Temp.	-20°C to +60°C					
Humidity	10% -90% RH (no condensation)					
Electrical Characteristic						
Operation Voltage	DC 12V					DC 5V
Current Consumption	Max. 1.2A	Max. 500mA	Max. 1.7A	Max. 0.6A	Max. 1.3A	Max. 500mA
System Compatibility						
ActiveSync	Windows 2000 / XP					
Mobile Device Center	Windows Vista /7/8					