



**Fiscal Suggestion  
3 inch Impact Dot  
POS Printer**

**SRP-270**



**HIGHLIGHTS**

- Match the model to your application with three impact printer models
  - SRP-270A: Tear bar
  - SRP-270C: Auto-cutter
  - SRP-270D: Auto-cutter with spooler
- High operational reliability (1.8 million lines MCBF)
- Reduce waiting time with its fast output printing 40 columns at 4.6 lines per second
- SRP-270D type version automatically spools printed paper into a conveniently storable roll.
- Produce flawless pre-printed documents with its black mark sensor.
- Easy to install ribbon cartridge (Black / Black & Red)

*The BIXOLON SRP-270 is a high quality and reliable impact dot POS printer (spooler option). The SRP-270 is an ideal printer for point of sale and hospitality applications. The modular user-friendly design, graphics capability, and 4.6 lps print speed offer reliable high performance in a compact, lightweight design. With the fast moving technology of today it is important to have simple integration of peripheral devices. The SRP-270 receipt printer is no exception; drivers are available for Windows and OPOS. Other features of the SRP-270 receipt printer include a paper end sensor that automatically alerts the user when the printer is out of paper, a tear-bar or auto-cutter, and the ability to print one original receipt plus two copies.*

**SPECIFICATIONS**

**PRINT**

- PRINTING METHOD : 9 Pin Serial Dot Matrix
- PRINTING SPEED : 4.6 lps
- RESOLUTION : Horizontal Resolution : 80 dpi  
Vertical Resolution : 144 dpi
- CHARACTER SIZE (W X H dots): Font A : 9 x 9 / Font B : 7 x 9  
Korean : 17 x 9 / Chinese : 16 x 16
- CHARACTERS PER LINE :  
FontA : 33 , Font B : 40  
Korean : 20, Chinese : 22 (3half dot : 21)
- CHARACTER SET : Alphanumeric Character : 95  
Extended Character : 128 x 7 pages  
International Character : 32

**PAPER**

- WIDTH : 76 ± 0.5mm
- PAPER ROLL DIAMETER : Max Ø 83.0mm
- PAPER LOADING : Easy Paper Loading

**RELIABILITY**

- PRINTER UNIT : 18 million lines
- HEAD : 300 million dots / wire
- AUTO CUTTER : 1 million cuts

**INTERFACE** : Serial(RS-232C / RS-485), Parallel (IEEE1284), USB

**EMULATION** : BXL / POS

**DRIVER** : Windows, OPOS

**SENSOR** : Paper End Sensor

**DRAWER PORT** : 2 ports

**POWER SUPPLY (SMPS)** : AC 100~240V / DC 24V, 1.5A

**DIMENSIONS (W X L X H mm)**

- SRP-270A : 160 x 249 x 130
- SRP-270C : 160 x 249 x 149
- SRP-270D : 160 x 295 x 160

**OPERATING TEMPERATURE** : 0~45°C / 32~113°F

**OPTION**

- RIBBON CARTRIDGE (RRC-201B/RRC-201BR)
- BIXOLON MELODIST (RMB-100)



*We Create Value!*